Ï»¿

Epple Maschinen TB 23 400V - 210 0123 ÎšÎ¿Î»Ï‰Î½Î¬Ï„Î¿ Î´Ï•Î¬Ï€Î±Î½Î¿ 550W

€648,0

Epple Maschinen TB 23 400V - 210 0123 ÎšÎ¿Î»Ï‰Î½Î¬Ï„Î¿ Î´Ï•Î¬Ï€Î±Î½Î¿ 550W

Î•Ï€Î±Î³Î³Î»Î¼Î±Ï„Î¹Î°ÏŽÎ½ Ï€Ï•Î¿Î´Î¹Î±Î³Ï•Î±Ï†ÏŽÎ½ Î“Î»Ï•Î¼Î±Î½Î¹Î°Î®Ï, Ï€Ï•Î¿Î-Î»Î»Ï…ÏƒÎ·Ï,

Î™Î´Î¹Î±Î¯Ï„Î»Î»Ï•Î± Ï‡Î±Ï•Î±Î°Ï„Î·Ï•Î¹ÏƒÎ„Î¹Î°Î±:
Â» ÏƒÏ„Î¹Î²Î±Ï•Î® Î°Î±Ï„Î±ÏƒÎ°Î»Ï…Î®
Â» Î¤Î± Î¼Î¿Î½Ï„Î-Î»Î± Ï„Ï‰Î½ 400V Ï€Î±Ï•Î-Ï‡Î¿Î½Ï„Î±Î¹ Î¼Î± Ï•Î¹ÏƒÏ„Ï‰Î»Ï•ÏŒÏƒÏ„Ï•Î¿Ï†Î·/ Î´Î»Î¾Î¹ÏŒÏƒÏ„Ï•Î¿Ï†Î· Ï€ÎµÏ•Î¹ÏƒÏ„Ï•Î¿Ï†Î®
Â» Î»Î³Î³Ï…Î·Î¼Î¿Î½Î· Î±Î°Ï•Î¯Î²Î»Î¹Î± Î¼Î» Î±Î½Î¿Ï‡Î® Î¼Î¹Î°Ï•ÏŒÏ„Ï•Î· Î±Ï€ÏŒ 0.02mm Î¼Î»Ï•Î·Î¼Î-Î½Î· ÏƒÏ„Î¿Î½ Î¬Î½Î¿Ï‚ Ï€ÎµÏ•Î¹ÏƒÏ„Ï•Î¿Ï†Î®Ï, Ï„Î¿Ï… Ï„ÏƒÎ¿Î°
Â» ÎŸÎ¿Î½Ï„Ï‰Ï„Î® Ï•Î¬Î³Î±Ï‚ Î³Î¹Î±Ï„Ï„Î¿Ï½ Î°Î¬Î¸Î¿Ï„Î· Ï„Î¿Ï… Ï„Ï•Î±Ï€Î¿Ï†Î¿Ï•
Â» Î¼Î±ÏƒÏ„Ï† Ï€Î¼Ï•Î¹ÏƒÏ„ÏŒÏ•Ï„Ï•Ï‰Ï†Î¿Ï, Î°Î±Î¹ Î±Î½Î¿Î°Ï•Î¼Ï½Î¿Ï, Ï€Î¬Î¸Î¿Ï†Ï•Ï‰Ï†Î¿Ï, Ï•Ï„Î¿Ï†Î¿Ï, Ï•Ï„Î¿Ï†Î¿Ï•
Â» Î Î¬Î³Î°Î¿Ï, Î¼Ï•Î³Î±ÏƒÏ†Î¿Ï•Ï, Î¼Î¼ Î¼Î³Î°Î¬Ï•Î¹Î± Î±Ï…Î»Î¬Î°Î¹Î± T
Â» Î¼Î±ÏƒÏ†Ï† Î²Î¬ÏƒÎ· Î¼Î³Î¬Ï‰Ï‰Î½ Î´Î¹Î±ÏƒÏ„Î¬Ï•Ï‰Ï‰Î½
Â» Î¼Ï…Î°Î¿Î»ÏŒÏ‡Ï•Ï·Ï•Ï„Î¿Ï, Î´Î¹Î±Î°ÏŒÏ€Ï„Î¿Ï, Î¼Î¼ Î±Ï€ÏŒÏ½Î¼Ï•Î³Î¿Ï€Î®ÏƒÎ· Ï‡Î±Î¼Î¼Î·Ï•Î»Î®Ï, Ï„Î¬Ï†Î·Ï, Î°Î±Î¹ Ï„Ï„Î¿Ï€Ï€Î¿Ï½ Î±Î½Î¬Ï†Î³Î°Î·Ï,
Â» Î¹Î¼Î¬Ï†Î½Ï„Ï, Ï„Ï•Ï€Î¿Ï…Ï•Ï…Ï… V Ï€Ï•Î¿Î¿ÏƒÏ„Ï•Î±Ï„Ï•Ï…Ï…Î¼Î·Î½Î¿Î¹ ÏƒÎ¼Ï•Î¯Ï²Î»Î·Î¼Î±
Â» Ï„Î±Ï‡Ï…Ï…Ï„ÏƒÎ¿Î° RÃ–HM 1-13mm
**Â» Î´Ï…Î½Î±Ï„Î¿Î¯ Î·Î»Î¼Î°Ï„Ï•Î¿Î¯ Î°Î¹Î½Î·Ï„Ï•Î®Ï•Î¼Ï, Î¿Î¼Î±Î»Î®Ï, Î»Î¼Î¹Ï„Ï•Î¿Ï…Ï•Ï…Ï… Ï€Ï•Î¿Ï…Ï•Ï…Ï…Ï„Ï•Î¿Ï…Ï…Ï…

Â» Ï†Ï‰Ï, ÎµÏ•Î³Î±ÏƒÎ¯Î±Ï,
Î¤Î•Î§Î•Î™Î§Î‘ Î§Î‘Î¡Î‘Î§Î¤Î—Î¡Î™Î£Î¤Î™Î§Î‘
Î´Î¹Î±Ï„Ï•Î·Ï„Î¹Î°Î· Î¹Î°Î±Î½ÏŒÏ„Î·Ï„Î± ÏƒÎµ Ï‡Î¬Î¬Ï…Î²Î±: 23 mm
Î´Î¹Î±Î´Ï•Î¿Î¼Î®: 80mm
ÎšÏŽÎ½Î¿Ï, Ï„ÏƒÎ¿Î°: MK 2
Î¤Î±Ï‡Ï•Ï„Î·Ï„Î¹Ï€Î¹Ï•Î¿Ï†Î®Ï, (rpm): 120 - 2.580
Î‘Ï•Î¹Î¸Î¼ÏŒÏ, Ï„Î±Ï‡Ï…Ï„Î®Ï„Ï‰Î½: 12
Î‘Ï…Ï„ÏŒÎ¼Î±Ï„Î· Ï€Ï•ÏŒÏ‰ÏƒÎ· Ï„ÏƒÎ¿Î°: ÏŒÏ‡Î¹
ÎµÏ•Ï•Î¿Ï, ÎµÏ•Î³Î±ÏƒÎ¯Î±Ï,: 180mm
Î´Î¹Î±ÏƒÎ¤Î¬ÏƒÎµÏ‰Î¹Ï, Ï„Ï•Î±Ï€Î¶Î¹Î¿Ï•: 290x290 mm
Î¼Î-Î³ÎµÎ¸Î¿Ï, ÏƒÏ‡Î¹Ï„Î¼Î®Ï, Î¤: 16mm
ÎšÎ»Î¯ÏƒÎ· Ï„Ï•Î±Ï€Î¶Î¹Î¿Ï•: +/- 45Â°
Î´Î¹Î¬Î¼Ï„Ï•Î¿Ï, Î°Î¿Î»ÏŽÎ½Î±Ï,: 80 mm
Î¹ÏƒÏ‡Ï•Ï, (50hz): 550 W
ÏƒÏ…Î½Î¿Î»Î¹Î°ÏŒ Ï•Ï´Î¿Ï,: 980 mm
ÎšÎ±Î¸Î±Ï•ÏŒ Î²Î¬Ï•Î¿Ï,: 56 kg
Ï„Î±ÏƒÎ·: 400V
Î°Ï‰Î´Î¹Î°ÏŒÏ,: 210 0123

Description
- solid construction suitable for craftsmen users
- precision of concentricity less than 0,02 mmmeasured in the spindle sleeve
- belt housing in steel, locked cover with safety shutdown
- powerful, smooth running electric motor, aluminum body with cooling fins
- 400 V model with forward and reverse run
- safety switch with low-voltage release and emergency stop
- rotating, tilting and inclinable massive working table with T-slots for 16 mm sliding blocks
- comfortable mechanical height adjustment of drilling table by toothed rack
- solid, large dimensioned base plate with T-slots, precise surface finishing
- working light
- RÃ–HM quick-action drill chuck supplied 1-13 mm
- drill chuck guard
- drill depth stop
Technical Data
drilling cap in steel 23 mm
Sleeve travel 80 mm
spindle taper MT 2
spindle speeds 120 - 2.580 min-1
automatic drilling feed no
working range 180 mm
table size 290 x 290 mm
T-slot size (table) 16 mm
T-slot number (table) 4
drilling table swivel +/- 45Â°
column diameter 80 mm
motor power 400 V / 50 Hz / 550 Watt
total height 980 mm
weight 56 kg
EAN 4260364290028

Î£Ï„Î¿Î¹Ï‡Î¼Î¯Î± Î Ï•Î¿Î¼Î·Î¸Î¼Ï…Ï„Î®