



Drilling cap in steel 23 mm  
sleeve travel 80 mm  
sleeve travel MK 2  
spindle speeds 120 - 2.580 (rpm)  
no. of speeds 12  
automatic drilling feed no  
working range 180 mm  
table size 290 x 290 mm  
T-slot size (table) 16 mm  
T-slot number (table) 4  
drilling table swivel +/- 45°  
column diameter 80 mm  
motor power 400 V / 50 Hz / 550 Watt  
total height 1.480 mm  
weight 60 kg  
EAN 4260364290066

### Description

- solid construction suitable for craftsmen and industrial use
- concentricity precision less than 0,02 mm measured in the spindle sleeve
- belt cover in steel with safety shutdown
- powerful, smooth running electric motor with cooling fins
- 400 V model with forward and reverse function
- safety switch with low-voltage release and emergency stop
- massive tilting, rotating and inclinable work table, T-slots for 16 mm sliding blocks
- comfortable mechanical adjustment of table height with toothed rack
- solid, large dimensioned base plate with T-slots, precise surface finishing
- working light
- RÄHM quick action drill chuck supplied as standard 1-13 mm
- drill chuck guard
- drill depth stop

### Technical Data

drilling cap in steel 23 mm  
sleeve travel 80 mm  
sleeve travel MK 2  
spindle speeds 120 - 2.580 min-1  
no. of speeds 12  
automatic drilling feed no  
working range 180 mm  
table size 290 x 290 mm  
T-slot size (table) 16 mm  
T-slot number (table) 4  
drilling table swivel +/- 45°  
column diameter 80 mm  
motor power 400 V / 50 Hz / 550 Watt  
total height 1.480 mm  
weight 60 kg  
EAN 4260364290066

<http://www.toolhouse.gr>