

TOOL HOUSE - **ΤΕΛ. +30.210.2774701**

toolhouse.gr

»

Epple Maschinen SBS 23 400V-215 0123 İ̂ŝġĀ»İ%oİ½İ-İ,,İġ İ'İ-İ€İ±İ½İġ 550W - İ'İ-İ»

€716,0



Epple Maschinen SBS 23 - 400V İ̂ŝġĀ»İ%oİ½İ-İ,,İġ İ'İ-İ€İ±İ½İġ 550W - İ'İ-İ»İ® İoİġİ½İ±

İ€İ±İŝİμİ»İ¼İ±İ,,İ'İoİŶİ½ İ€İoİġİ'İ±İŝİ±İİŶİ½ İ'İμİoİ¼İ±İ½İ'İoİ®, İ€İoİġİ-İ»İμİ...İfİ-İ,
 İ™İ'İ±İ-İ,,İμİoİ± İ±İ±İoİ±İoİ,,İ-İoİ'İfİ,,İ'İoİ±:
 Å» İfİ,,İ'İŶİ±İoİ® İoİ±İ,,İ±İfİoİμİ...İ®
 Å» İoİ± İ¼İġİ½İ,,İ-İ»İ± İ,,İ%oİ½ 400V İ€İ±İoİ-İ±İġİ½İ,,İ±İ' İ¼İμ Ι±İoİ'İfİ,,İμİoİ€İfİ,,İoİġİİ- / İ'İμİ¼İ'İ€İfİ,,İoİġİİ-
 İ€İμİoİ'İfİ,,İoİġİİ®
 Å» İμİoİŝİ...İ-İ¼İ-İ½İ- Ι±İoİoİ'İŶİμİ± İ¼İμ Ι±İ€İ€İoİ»İ'İfİ- İ¼İ'İoİoİ€İ,,İμİoİ- Ι±İ€İ€Ε 0.02mm
 Å» İŶİ'İġİ½İ,,İ%oİ,,İ® İoİ-İŝİ± İŝİfİ± İ,,İ-İ½ İoİ-İ μİ,,İ- İoİoİ¼İ'İfİ- İ,,İġİ... İ,,İoİ±İ€İμİŝİ'İġİoİ
 Å» İŶİ¼İ±İ»İ- İ€İμİoİ'İfİ,,İoİμİİ€İ¼İμİ½İġİ, İoİ±İ' Ι±İ½İ±İoİ»İ'İ½İ€İ¼İμİ½İġİ, İ€İ-İŝİoİġİ, İμİoİŝİ±fİ-İ±İ,
 Å» İ-İŝİoİġİ, İμİoİŝİ±fİ-İ±İ, İ¼İμ Ιμİŝİoİ-İoİfİ'İ± Ι±İ...İ»İ-İoİ'İ± T
 Å» İ¼İ±İfİİ-İ'İŶİ-İfİ- İ¼İμ Ι¼İμİŝİ-İ»İμİ, İ'İ'İ±İfİ,,İ-İfİμİ'İ,
 Å» İμİ...İoİġİ»İ€İ€İ±İoİ-İfİ,,İġİ, İ'İ'İ±İoİ€İ€İ,,İ-İ, Ι±İfİİ±İ»İμİ-İ±İ, İ¼İμ Ι±İ€İμİ½İμİoİŝİ€İ€İġİ'İoİfİ- Ι±İ±İ¼İ-İ»İoİ,
 İ,,İ-İfİ-İ, İoİ±İ' İfİ,,İġİ€ Ι±İ½İ-İŝİoİ-İ,
 Å» İ'İ¼İ-İ½İ,,İμİ, İ,,İoİ€İ€İ... V İ€İoİġİfİ,,İ±İ,,İμİ...İ¼İ-İ½İġİ' Ι±İ€İ€ Ι±İ,,İfİ-İ»İ'İ½İġ İ€İμİoİ'İŶİ»İ-İ¼İ±
 Å» İ,,İ±İ±İ...İ,,İfİġİ° RÅ-HM 1-13mm
 Å» İ'İ...İ½İ±İ,,İġİ-İ-İ»İμİoİ,,İoİ'İoİġİ' İoİ'İ½İ-İ,,İ®oİμİ, İġİ¼İ±İ»İoİ, İ»İμİ'İ,,İġİ...İoİŝİİ±İ,
 Å» İfİ,,İġİ€ İŶİ-İġİġİ...İ, İ'İ-İ-İ,,İoİ-İfİ-İ,
 Å» İ-İoİġİİ...İ»İ±İoİ,,İ®oİ±İ, İ,,İfİġİ°
 Å» İ'İ'İoİ, Ιμİoİŝİ±fİ-İ±İ,
 İoİŝİoİ™İŝİ' İŝİ'İġİ'İŝİoİ-İİ™İ€İİ™İŝİ'

Drilling cap in steel 23 mm
Sleeve travel 80 mm
Sleeve travel MK 2
Spindle speeds 120 - 2.580 (rpm)
No. of speeds 12
Automatic drilling feed no
Working range 180 mm
Table size 290 x 290 mm
T-slot size (table) 16 mm
T-slot number (table) 4
Drilling table swivel +/- 45°
Column diameter 80 mm
Motor power 400 V / 50 Hz / 550 Watt
Total height 1.480 mm
Weight 60 kg
EAN 4260364290066

Description

- solid construction suitable for craftsmen and industrial use
- concentricity precision less than 0,02 mm measured in the spindle sleeve
- belt cover in steel with safety shutdown
- powerful, smooth running electric motor with cooling fins
- 400 V model with forward and reverse function
- safety switch with low-voltage release and emergency stop
- massive tilting, rotating and inclinable work table, T-slots for 16 mm sliding blocks
- comfortable mechanical adjustment of table height with toothed rack
- solid, large dimensioned base plate with T-slots, precise surface finishing
- working light
- R&H quick action drill chuck supplied as standard 1-13 mm
- drill chuck guard
- drill depth stop

Technical Data

drilling cap in steel 23 mm
sleeve travel 80 mm
sleeve travel MK 2
spindle speeds 120 - 2.580 min-1
no. of speeds 12
automatic drilling feed no
working range 180 mm
table size 290 x 290 mm
T-slot size (table) 16 mm
T-slot number (table) 4
drilling table swivel +/- 45°
column diameter 80 mm
motor power 400 V / 50 Hz / 550 Watt
total height 1.480 mm
weight 60 kg
EAN 4260364290066

<http://www.toolhouse.gr>