Ï»¿

Epple Maschinen KKS 315 SA-2402315 Î”Î¹Ïƒ Î°Î¿Ï€Ï•Î¯Î¿Î½Î¿ Ï…Î³Ï•Î¬Ï, Î°Î¿Ï€Î®Ï, 1,5kW

€4 340,0

Epple Maschinen KKS 315 SA - 240 2315 Î”Î¹Ïƒ Î°Î¿Ï€Ï•Î¯Î¿Î½Î¿ Ï…Î³Ï•Î¬Ï, Î°Î¿Ï€Î®Ï, 1500W
Î™Î¯Î±Î¯Ï„Î¼Ï•Î± Ï‡Î±Ï•Î±Î°Ï„Î·Ï•Î¹Ïƒ Î¹Ï•Î¹Ï¬Î¹Î°Î¬:
- 2 Ï„Î±Ï‡Ï•Ï„Î·Ï„Î¼Ï, Î°Î¹Î½Î·Ï„Î®Ï•Î±
- Î·Î»Î¼Î°Ï„Ï•Î¹Î°Î® Ï´Ï…Î°Ï„Î¹Î°Î® Î±Î½Ï„Î»Î¯Î±
- Î°Î¼Ï†Î±Î»Î® Î³Ï•Î®Î³Î¿Ï•Î·Ï, Î¸Î·Ïƒ Î·Ï, 90Â°Î´Î¾Î¼Î¹Î¬, 90Â° Î±Ï•Î¹Ïƒ Ï„Î¼Ï•Î¬
- Ï…Ï´Î·Î»Î®Ï, Ï€Î¿Î¹ÏŒÏ„Î·Ï„Î±Ï, Î¬Î¬Ï•Î±Ï…Ïƒ Ï„Î¿Ï, Î°Î¹Î½Î·Ï„ÏŒÏ, Ï€Ï•Î¿Ï†Ï…Ï„Î»Î±Î°Ï„Î®Ï•Î±Ï, Î¼Ï Ï„Î±Ï‡Ï…Î¼Î¹Î±Ï‡Î¼Ï„Î¿ Ï…Ï·Î½ Î±Ï‡Ï…Î¿Î¯Î¿ Ï€Ï•Î¿Ï†Ï…Ï„Î®
- Î±Ï…Ï„ÏŒÏ„Î¼Î¿ Î¿Î»Î¼Ï´Î¹Î¼Î¿ & Î¬Î½Î¿Î¹Î³Î¼Î¿ Ï„Î¿Ï… Ï€Î¿Ï…Ï•Î¹Î®Î¼Î¿Ï, Î±Ïƒ Î±Ï†Ï…Î»Î¼Ï´Î¿Ï, Ï„Î¿Ï… Ï€Ï•Î¹Î¿Î½Î¹Î¿Ï• - Ï…Ï´Î·Î»Î® Î±Î½Ï„Î¿Ï‡Î® Ïƒ Î¼ Î¸Ï•Î±Ï•Ïƒ
- Î°Î¼Î½Ï„Ï•Î¹Î°ÏŒÏ Ïƒ†Î¯Î¾Î¹Î¼Î¿Ï, Î¼Î¿ 4 Î±Î½Î¼Î¾Î¬Ï•Ï„Ï, Î¼Î¿ Ï•Ï…Î¸Ï„Ï•Ï…Ï¶ÏŒÏ¼Î¼Î½Î¼Ï, Ïƒ Î¹Î±Î³ÏŽÏ½Î¼Ï,
- Î±Î°Ï•Î¹Î²Î®Ï,Ï, Î±Ï…Ï„Ï¿Î°Î¼Î½Ï„Ï•Î¬Î¶ÏŒÏ¼Î¼Î½Î· Î´Î¹Î®Î»Î® Î¼Î¿Î³Î³Î¼Î½Î·, Ï„Î¼Ï„Ï•Î±Ï€Î»Î¿Î¯ Î¿Î´Î·Î³Î¿Î¯
- Î¿Ï•Î¹Î¶ÏŒÏ¼Ï„Î¼Ï, Î°Î¹Î½Î·Ï„Ï•Î¬, Ïƒ Î¹Î±Ï‡Ï…Ï½Î¼Ï, Î³Î¹Î± Î¼Î¿Î³Î¹Ïƒ Ï…Ï· Ïƒ…Î³Î°Ï•Î¬Ï•Ï· Ï…Î»Î¹Î°Î¿Ï• Ïƒ Ï„Ï, Ï€Ï•Î»Î±ÏŠÏ½Î¬Ï, Î°Î¿Ï€Î¬Ï,
- Î²Ï•Ï•Î¬Ï Î¼Ï€Î±Î³Î³Î¼Î»Î¼Î¼Ï½Î¼Ï, Î²Î®Î° Î²Î¬Ïƒ, Î¬Ï„Ï„Î¿Ï…Î¿Ï½Î¼Ï Ïƒ Ï…Î½Î±Ï…Ï…Î¿Ï½Î¼Ï Ï•Î±Î¿Ï…Î»ÏŒÏ´Ï•Î¿Î¼Î¿Ï…Ï,
- Î²Î¬Ïƒ Ïƒ Ï„Ï,Î®Ï•Ï•Î¾Î¬Ï, Î¼Î¼ Î¼Ï½Ïƒ‰Î¼Î±Ï„Ï½Î¬Ï Ïƒ Ï…Ï…Ïƒ°Î¼Ï…Î® Ï´Ï•Î¾Î¬Ï,
**- Î¼Î¼Ï„Î¬Î´Î¿Ïƒ Ï…Ï…Ï…Ï¼Ï€Ï•Ï„Î¿Ï· Î¿Î»Î¹Ïƒ Î®Ïƒ Ï…Ï½Î¿Ï•Ï…Ï…Ï½Î¿Ï•Ï…Ï½Î¿Ï•Ï…Ï½Î¿Ï•

Îµï•ï•Î¿ï, Î°Î¿ï€Î®ï, ïƒï„Î¹ï, 90Â° ï€Î±ï•Î±Î»Î·Î»Î¿Î³ï•: 70 x 70mm
Îµï•ï•Î¿ï, Î°Î¿ï€Î®ï, ïƒï„Î¹ï, 45Â° ïƒï„ï•Î¿Î³Î³ï…Î»ïŒ: 70mm
Îµï•ï•Î¿ï, Î°Î¿ï€Î®ï, ïƒï„Î¹ï, 45Â° ï„Îµï„ï•Î¬Î³ï‰Î½Î¿: 70x70mm
Îµï•ï•Î¿ï, Î°Î¿ï€Î®ï, ïƒï„Î¹ï, 45Â° ï€Î±ï•Î±Î»Î·Î»Î¿Î³ï•: 80x70mm
Î¬Î½Î¿Î¹Î³Î¼Î¼Î± Î¼Î-Î³Î³Îµï½Î·ï‚: 140mm
ï„Î±ï‡ï•ï„Î·ï„Î± Î´Î¯ïƒÎ°Î¿ï…: 19/38rpm
Î¹ïƒï‡ï•ï‚: 400 V / 50 Hz / 750 W /1,5 kW
Î´Î¹Î±ïƒï„Î¬ïƒÎµÎ¹ï‚: 905x550x1.350mm
ï•ï´Î¿ï, Îµï¹ïƒïŒÎ´Î¿ï…: 930 mm
Îšï±Î¸Î±ï•ïŒ Î²Î¬ï•Î¿ï‚: 270kg
EAN: 4260364290899
Î°ï‰Î´Î¹Î°ïŒï‚: 240 2315
Description:
- 2-speed motor
- automatically closing & opening safety enclosure of the saw blade: high-grade and fracture proof
- precise self-centering double vice, quadruple guides
- heavy-duty stand, prepared to connect to roller stands
- transmission with slip clutch to avoid damage of the saw blade
- coolant system integrated in the stand
Specifications:
Saw blade diameter: max. 315 mm
Saw blade bore: 40 mm
Rotatable head: Â± 90 Â°
Sectional area of â€‹â€‹90 Â° around: 70 mm
Sectional area of â€‹â€‹90 square degrees: 90 x 80 mm
Sectional area of â€‹â€‹90 Â° rectangular: 70 x 70 mm
Cutting range 45 Â° around: 70 mm
Cutting range 45 Â° square: 70 x 70 mm
Cutting range 45 Â° rectangular: 80 x 70 mm
Open vise: 140 mm
Number of revolutions: 19/38 min -1
Inlet height: 930 mm
Engine power: 400V/50Hz / 750Watt /1,5 kW
Dimensions (D x W x H): 905 x 550 x 1,350 mm
Weight: 270 kg
EAN 4260364290899

Î£ï„Î¿Î¹ï‡Îµï¯Î± Î ï•Î¿Î¼Î·Î¸Îµï…ï„Î®