

???? ?????????? 1119,90 €

???? ?????????? ?????? ??? 903,15 €

????? ?????????????? ?????????? (Vario) ?? ?????????? ??????
????????????? ?? ?????????? ?????????? ?????????? ??????????
????????????? ?? ?????????? (? ? ?????? ?? ? ?????? ?????? V ???
????????????? ?????? ?????????????? ?? ??????. ?????????? ?? ?
????????? ??????????

??????????

HOLZMANN MASCHINEN ED400FD_230V ?????? ?????????????? ??????????

????? ?????????????? ?????????? (Vario) ?? ?????????? ?????? ?????????? ?? ?????????? ?????????? ?????????? ?????????? ??????????
????? ?????????? ?????? ?????????? (< 0,009 mm) ?? ?????????? ?????? ?????????? ??????????????. ?????????? ?? ?????????? ??????????
????????????? ?? ?????????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? ?????? V ?? ?????

????????????????? ?????????????? ?????????????? ??????????????

highlights:

- serially equipped with leadscrew for thread cutting and automatic longitudinal feed
- induction-hardened and precision ground prismatic bed way guides
- hardened main spindle bedded with adjustable taper roll bearings
- high spindle centricity (< 0,009 mm) assures maximal turning accuracy
- spindle speed steplessly adjustable, speed can be read off conveniently from digital speed display
- comes with change gears delivering an exceptionally broad thread cutting range
- guides conveniently adjustable via V-ledges ensuring precision for many years powerful, maintenance free motor with undervoltage release
- smooth power transmission delivers constant torque
- tailstock can be adjusted for taper turning
- CW/CCW run mode
- Note: Machine runs at half speed when reversing.

included in delivery: 3-jaw chuck Ø 100mm, 4-way tool post, dead center MT3, dead center MT2, chuck guard, chip tray, change gears, tools

technical details:

turning machines:

- range of metric threads in mm (18 S): 0.5-3
- lathe spindle speed in min-1: 50-2500
- max. swing over cross slide in mm: 110
- range of inch threads: 8-44
- tailstock cone: MK2/MT2
- spindle nose mount: MK3/MT3
- spindle bore in mm: 21
- carnage travel in mm: 80
- tailstock sleeve travel: 55
- cross slide travel in mm: 80
- compound slide travel in mm: 85
- distance between centers in mm: 400
- max. swing over bed in mm: 210

measurements:

- bed width in mm: 100
- total dimensions in mm: 930x390x370

motor data:

- motor power s1 in W: 450
- voltage: 230V

weight:

- gross weight in kg: 75
- net weight in kg: 70

packaging:

length in mm: 900

width in mm: 450

height in mm: 460

general data:

EAN code: 9120039901329