

???? ?????????? 2699,00 €

???? ?????????? ?????? ??? 2176,61 €

????? ?????????????? ????????? (Vario) ?? ?????????? ?????
????????????? ?? ????????? ?????? ??????. ?????? ?????????
????????????? ?? ????????? ?? ?????????????? ?????? ????????? ??????
?????????????. ????????? ?? ??? 2 ????????? ??????????
?????????????, ?????????

???????????

HOLZMANN MASCHINEN ED750FD_230V ?????? ?????????????????? ??????????

?????? ?????????????????? ????????? (Vario) ?? ?????????????? ?????? ?????????????? ?? ?????????? ?????????? ??????
????????? ?????????? ?????????????????? ?? ?????????? ?? ?????????????????? ?????? ?????????? ?????????? ?????????? ??????????
????? ??? 2 ?????????? ?????????????? ??????????????????, ?????????? ?????????????? ?????????????? ??? ?????????????? ?????? ??????
?????? ?????????? ??????????????????. ?? ?????????? ?? ?????????? ?????? V ??? ?????????????????? ?????? ?????????????? ???
?????????. ?????????????? ?? ??? ?????????? ?????????????? ?? ?????????????????? ?????????? ??????. ?? ?????? ?????????????? ?????
?????????????????. ? ?????????? ?????????? ?????????? ?????????? ?????????? ??? **HOLZMANN MASCHINEN ED 750FADQ**
????????????????????? ?????????????????? ?????????????????? ?????????????????.

highlights:

- solid and rugged cast iron set up
- variable speed adjustable via potentiometer
- speed indication via LCD-display
- resistant and induction-hardened machine bed
- stand with two cabinets included in delivery, modern design
- max. turning diameter 250mm, bed width 135mm
- lead screw cover ensures a long durability and accuracy over many years
- spindle bore 25mm, spindle taper MT3, tail stock MT2
- machine able to cut metric threads
- included in delivery: stand, 3-jaw chuck Ø125mm, steady rest, follow rest change gears, 2pcs dead centres, inner and outer jaws, 4-way tool post, lead screw cover, chuck guard with window, 4-jaw chuck, face plate

technical details:

turning machines:

range of inch threads: 8-56
range of metric threads in mm/r: 0,4-3,5
lathe spindle speed in min-1: 0-2500
tailstock cone: MK2/MT2
spindle nose mount: MK3/MT3
spindle bore in mm: 25
distance between centers in mm: 750
max. swing over bed in mm: 250
center height in mm: 125

measurements:

bed width in mm: 135
total dimensions in mm: 1350x480x550

motor data:

motor power s1 in W: 730
motor power s6 in W: 1000
voltage: 230V

weight:

gross weight in kg: 214

net weight in kg: 200

packaging:

length in mm: 1.385

width in mm: 625

height in mm: 565

general data:

EAN code: 9120039900902